

SHURFLO AQUA KING™ II Jr 2.0 MARINE FRESH WATER PUMP – PRODUCT TECHNICAL DATA SHEET

 OEM:
 4129-110-A02

 AFTERMARKET:
 4129-110-B02 ← old 68009C - 2901-0212



APPLICATION:

Multi-fixture Marine fresh water pump installation. This pump may be used for general fresh water transfer

PUMP DESIGN:

Туре:	4 Chamber Diaphragm pump	
Ports:	1/2"-14 NPSM-Male	
Liquid:	54°C [130°F] Max	
Dry-Prime:	1.82 M [6 feet]	_
Run Dry:	Yes	
Inlet Pressure:	2.06 Bar [30 PSI]	_

ELECTRICAL:

Motor:	12V DC Permanent Magnet, Intermittent Duty
Protection:	Thermal Overload, Automatic Restart
Leads:	14 AWG, 37cm [14 ¾"] Red +, 38cm [15"] Black
Fuse:	5 Amp Recommended
Control:	Shut-Off 1.37 Bar [20 PSI] ± 0.13 Bar [2 PSI]
	Re-start 0.68 Bar [10 PSI] [1.0 Bar] ± [2 PSI]

MATERIALS OF CONSTRUCTION:


Housings:	Polypro
Valves/Seals:	EPDM
Diaphragm:	Santoprene
Hardware:	Stainless Steel

AGENCY APPROVALS:

Ignition Protection 8846, CE, IMCI Certified

SHIPPING INFORMATION:

Approx. Net Weight:1.92 Kg [4.25 lbs.] ea.Carton Qty.:6Approx. Carton Weight:12.2 Kg [27 lbs.]Approx. Carton Size:61cm x 46cm x 15cm [24"L X 18"W X 6"H]






N	Description	De et Namel est
Number	Description	Part Number
*1	Upper Assembly	94-800-41
2	Valve Assembly	94-800-01
3	Drive Assembly	94-800-25
4	Motor/Gasket	94-71-003-07
*1,2,3	Pump Head	94-800-32
Not Shown	Check Valve	94-800-03

*With preset switch adjustment

RELATED DOCUMENTS:

Catalog:	MS-030-140
App Guide Sheet :	MS-020-005
Installation Manual:	911-1052
Aftermarket Warranty:	911-1045



PENTAIR

FLOW MANAGEMENT SOLUTIONS

3545 Harbor Gateway South, Suite 103, Costa Mesa, CA 92626, (800) 854-3218 www.SHURFLO.com

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.