


SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** SEATEC EPOXY LEICHT SPACHTEL Härter
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Hardener for coatings
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**

SVB Spezialversand für Yacht- und Bootszubehör GmbH
Gelsenkirchener Str. 25-27
28199 Bremen
Germany
Tel. +49 (0) 421 57 29 0-0
info@svb.de
- 1.4 Emergency telephone number:**

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302
Eye Dam. 1: Serious eye damage, Category 1, H318
Skin Corr. 1B: Skin corrosion, Category 1B, H314
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
- 
- Hazard statements:**
Acute Tox. 4: H302 - Harmful if swallowed
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage
Skin Sens. 1A: H317 - May cause an allergic skin reaction
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P280: Wear protective gloves/protective clothing/eye protection/face protection
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively
- Substances that contribute to the classification**
3-aminomethyl-3,5,5-trimethylcyclohexylamine; Benzyl alcohol; Cycloaliphatic amine; Salicylic acid
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**





SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 2855-13-2 EC: 220-666-8 Index: 612-067-00-9 REACH 01-2119514687-32- xxxx	3-aminomethyl-3,5,5-trimethylcyclohexylamine ¹ Self-classified	25 - <50 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317 - Danger 	
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH 01-2119492630-38- xxxx	Benzyl alcohol ¹ Self-classified	10 - <25 %
	Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319 - Warning 	
CAS: 38294-64-3 EC: 500-101-4 Index: Non-applicable REACH 01-2119965165-33- xxxx	Cycloaliphatic amine ¹ Self-classified	10 - <25 %
	Regulation 1272/2008 Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger 	
CAS: 69-72-7 EC: 200-712-3 Index: Non-applicable REACH 01-2119486984-17- xxxx	Salicylic acid ¹ Self-classified	1 - <10 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318 - Danger 	

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 5: FIREFIGHTING MEASURES (continued)

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	47 mg/kg	Non-applicable	9,5 mg/kg	Non-applicable
	Inhalation	450 mg/m ³	Non-applicable	90 mg/m ³	Non-applicable
Cycloaliphatic amine CAS: 38294-64-3 EC: 500-101-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,14 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,98 mg/m ³	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	16 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	Oral	Non-applicable	Non-applicable	0,526 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	25 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Dermal	28,5 mg/kg	Non-applicable	5,7 mg/kg	Non-applicable
	Inhalation	40,55 mg/m ³	Non-applicable	8,11 mg/m ³	Non-applicable
Cycloaliphatic amine CAS: 38294-64-3 EC: 500-101-4	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,175 mg/m ³	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Oral	4 mg/kg	Non-applicable	1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4 mg/m ³	0,2 mg/m ³

PNEC:

Identification					
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	STP	3,18 mg/L	Fresh water	0,06 mg/L	
	Soil	1,121 mg/kg	Marine water	0,006 mg/L	
	Intermittent	0,23 mg/L	Sediment (Fresh water)	5,784 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,578 mg/kg	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L	
	Soil	0,456 mg/kg	Marine water	0,1 mg/L	
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,527 mg/kg	
Cycloaliphatic amine CAS: 38294-64-3 EC: 500-101-4	STP	10 mg/L	Fresh water	0,0111 mg/L	
	Soil	0,00279 mg/kg	Marine water	0,00111 mg/L	
	Intermittent	0,111 mg/L	Sediment (Fresh water)	0,0456 mg/kg	
	Oral	1 g/kg	Sediment (Marine water)	0,00456 mg/kg	
Salicylic acid CAS: 69-72-7 EC: 200-712-3	STP	162 mg/L	Fresh water	0,2 mg/L	
	Soil	0,166 mg/kg	Marine water	0,02 mg/L	
	Intermittent	1 mg/L	Sediment (Fresh water)	1,42 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,142 mg/kg	

- CONTINUED ON NEXT PAGE -

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



8.2 Exposure controls:

A.- General security and hygiene measures in the work place



As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 EN 168:2001 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk		EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	<input type="checkbox"/> White
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	233 °C
Vapour pressure at 20 °C:	3 Pa
Vapour pressure at 50 °C:	46 Pa (0 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	700 kg/m ³
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	5,49 cP
Kinematic viscosity at 20 °C:	3,9 cSt
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	380 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Cycloaliphatic amine CAS: 38294-64-3 EC: 500-101-4	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LD50 oral	1030 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	500 mg/kg	Rat
	LD50 dermal	2500 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Salicylic acid CAS: 69-72-7 EC: 200-712-3	LD50 oral	891 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LC50	110 mg/L (96 h)	Leuciscus idus	Fish
	EC50	388 mg/L (48 h)	N/A	Crustacean
	EC50	Non-applicable		
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LC50	646 mg/L (48 h)	Leuciscus idus	Fish
	EC50	400 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae
Cycloaliphatic amine CAS: 38294-64-3 EC: 500-101-4	LC50	10 - 100 mg/L (96 h)		Fish
	EC50	10 - 100 mg/L		Crustacean
	EC50	10 - 100 mg/L		Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	BOD5	Non-applicable	Concentration	7 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	8 %
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %

12.3 Bioaccumulative potential:

- CONTINUED ON NEXT PAGE -

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	0
	Pow Log	1.1
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	Koc	928	Henry	4,46E-4 Pa·m ³ /mol
	Conclusion	Low	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,444E-2 N/m (207,25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity, HP8 Corrosive, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1760
14.2 UN proper shipping name: CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
Special regulations: 274
Tunnel restriction code: E
Physico-Chemical properties: see section 9
Limited quantities: 1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



- 14.1 UN number:** UN1760
14.2 UN proper shipping name: CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
Special regulations: 274
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:



- 14.1 UN number:** UN1760
14.2 UN proper shipping name: CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Salicylic acid (Product-type 2, 3, 4)

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage

H318: Causes serious eye damage

H317: May cause an allergic skin reaction

H302: Harmful if swallowed

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage

Eye Irrit. 2: H319 - Causes serious eye irritation

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Sens. 1: H317 - May cause an allergic skin reaction

Skin Sens. 1A: H317 - May cause an allergic skin reaction

Classification procedure:

Skin Corr. 1B: Calculation method

Eye Dam. 1: Calculation method

Skin Sens. 1A: Calculation method

Acute Tox. 4: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SEATEC EPOXY LEICHT SPACHTEL Härter

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -