

# Product Data

## Hempel's Anti-Slip Pearls 69070



**Description:** HEMPEL'S ANTI-SLIP PEARLS 69070 can be added to all types of paint where a non-slip surface is required.

**Recommended use:** Mix with Hempel's topcoats and varnishes to obtain non-slip finishes on decks other surfaces.

**Availability:** Part of European Yacht assortment. Local availability subject to confirmation.

### PHYSICAL CONSTANTS:

Shade nos/Colours: 10000/ White.

Flash point: None.

Specific gravity: 1 kg/litre [7.9 lbs/US gallon]

VOC content: 0 g/l [0 lbs/US gallon]

*The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.*

### APPLICATION DETAILS:

Application method: Roller

**Safety:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.

# Product Data

## Hempel's Anti-Slip Pearls 69070



### REMARKS:

Application(s): Stir ANTI-SLIP PEARLS thoroughly into the paint until a uniform mixture has been obtained. Use 50 g ANTI-SLIP PEARLS for 3/4 l of paint. Usually one coat is sufficient but if a more coarse structure is required, apply one more coat.

Overcoating: If the maximum overcoating interval is exceeded, clean with fresh water and allow to dry. Light abrade and remove all dust prior to repainting.  
If surface has been contaminated by oils and pollutants, thoroughly remove with suitable detergent, rinse with fresh water and allow to dry. Light abrade and remove all dust prior to repainting.

Note: **HEMPEL'S ANTI SLIP PEARLS 69070**

ISSUED BY: HEMPEL A/S

6907010000

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" available on [www.hempel.com](http://www.hempel.com). Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.