

LENCO ELECTRIC HATCH LIFTS

PRODUCT INFORMATION DOWNLOAD



file shown
20760-001 through 20789-001.



Electric Hatch Lifts 12 & 24-Volt Models

12 and 24-Volt with 2' leads & deutsch connectors. Inline motor design delivers over 500 lbs. of force. Includes vandar mounting brackets & stainless steel pull pins.

Hatch Lift Features:

- ▶ NEW - Clear anodized aluminum tubing
- ▶ Sizes available with 4" thru 30" stroke. Available in 12- and 24-volt
- ▶ Complete with 2' lead and Deutsch plug (actuator extension harnesses are available in lengths of 7', 14', 20', 26', 32' and 45')
- ▶ Clutchless ball screw design will not drift, never binds and runs in sync on dual lift applications
- ▶ Inline motor design delivers over 500 lbs. (226.79 Kg) of force
- ▶ Waterproof, made entirely of non corrosive materials
- ▶ Ball screw spins freely when hatch is fully opened or closed eliminating limit switches and burned out motors
- ▶ Vandar mounting brackets with stainless steel pull pins
- ▶ Powdered metal gears for strength and precision
- ▶ Stainless steel ram locks in any position
- ▶ Amp draw 10 amps at 12-volt and 5 amps at 24-volt
- ▶ CE-certified and ABYC compliant
- ▶ O-ring sealed at 100 psi

Electric Hatch Lifts with 2' Leads and Deutsch connectors

L.O.A. = Length Overall, measuring from top bracket to bottom bracket

12-Volt Models

Lenco Part#	Superseded Part#	L.O.A. Retracted	Approximate Stroke	L.O.A. Extended
20760-001	HL-400	15"	4"	19"
20762-001	HL-600	20"	6"	26"
20764-001	HL-800S	20"	8"	28"
20766-001	HL-800	24"	8"	32"
20768-001	HL-1200S	24"	12"	36"
20770-001	HL-1200	29"	12"	41"
20772-001	HL-1400	33"	14"	47"
20774-001	HL-1600S	29"	16"	45"
20776-001	HL-1600	33"	16"	49"
20778-001	HL-2000S	33"	20"	53"
20780-001	HL-2000	37"	20"	57"
20782-001	HL-2400S	37"	24"	61"
20784-001	HL-2400	41"	24"	65"
20786-001	HL-2600	47"	26"	73"
20788-001	HL-3000	47"	30"	77"

24-Volt Models

20761-001	HL-400/24V	15"	4"	19"
20763-001	HL-600/24V	20"	6"	26"
20765-001	HL-800S/24V	20"	8"	28"
20767-001	HL-800/24V	24"	8"	32"
20769-001	HL-1200S/24V	24"	12"	36"
20771-001	HL-1200/24V	29"	12"	41"
20773-001	HL-1400/24V	33"	14"	47"
20775-001	HL-1600S/24V	29"	16"	45"
20777-001	HL-1600/24V	33"	16"	49"
20779-001	HL-2000S/24V	33"	20"	53"
20781-001	HL-2000/24V	37"	20"	57"
20783-001	HL-2400S/24V	37"	24"	61"
20785-001	HL-2400/24V	41"	24"	65"
20787-001	HL-2600/24V	47"	26"	73"
20789-001	HL-3000/24V	47"	30"	77"

SWITCH KITS SOLD SEPARATELY



Single Rocker Switch for hatch lifts with two 30" non-terminated power leads.

- 15096-001 Single hatch lift applications
- 15098-001 Twin hatch lift applications

OPTIONAL HATCH LIFT ACCESSORIES AVAILABLE



Optional stainless steel non-locking slide bracket for hatch lifts
70381-001

In case of power failure, this bracket allows you to pull the hatch open 4" in order to remove pull pin for access.