



Safety Data Sheet dated 3/6/2020, version 5
Regulation (EU) 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Identification of the mixture:

Trade name: ALTURA UV MAT
Trade code: 648.000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Varnish

1.3. Details of the supplier of the safety data sheet

Company:

BOERO BARTOLOMEO S.p.A. - Via Macaggi 19 - 16121 Genova - Tel. +39 010 55001 - Fax +39 010 5500305 - CF/P. IVA/REG. IMPRESE DI GENOVA 00267120103

Competent person responsible for the safety data sheet:

sicurezzaprodotti@boero.it

1.4. Emergency telephone number

BOERO BARTOLOMEO S.p.A. - Tel.+39 010 55001

opening hours: Monday - Tuesday 9.00 am - 5.00 pm

UK: in an emergency the enquirer should call NHS 111/24/Direct (free-to-call medical helplines) or a doctor.

MALTA: tel. 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Flam. Liq. 3, H226 Flammable liquid and vapour.

STOT SE 3, H336 May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire use CO2 or chemical powder. Never use water.

P403+P235 Store in a well-ventilated place. Keep cool.

648.000/5

Page n. 1 of 13

Safety Data Sheet

ALTURA UV MAT

P405 Store locked up.

P501 Dispose of contents/container according to local regulations.

Special Provisions:

None

Contains

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

1-methoxy-2-propanol; monopropylene glycol methyl ether

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime: May produce an allergic reaction.

Hydroxyphenyl-benzotriazole derivatives - EC number 400-830-7: May produce an allergic reaction.

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

Adverse physicochemical, human health and environmental effects:

The main adverse physical-chemical effects for human health and the environment are listed in accordance with Sections 9 to 12 of the safety data sheet

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 30% - < 40% hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

REACH No.: 01-2119463258-33-XXXX, EC: 919-857-5

Flam. Liq. 3 H226 Flammable liquid and vapour.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

STOT SE 3 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

DECLP (CLP)*

>= 5% - < 7% hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

EC: 927-632-8

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

>= 3% - < 5% 1-methoxy-2-propanol; monopropylene glycol methyl ether

REACH No.: 01-2119457435-35-XXXX, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

>= 1% - < 2.5% neodecanoic acid, zirconium salt

648.000/5

Page n. 2 of 13

Safety Data Sheet

ALTURA UV MAT

CAS: 39049-04-2, EC: 254-259-1
Skin Irrit. 2 H315 Causes skin irritation.

>= 1% - < 2.5% xylene [4]

REACH No.: 01-2119488216-32-XXXX, CAS: 1330-20-7, EC: 215-535-7
Flam. Liq. 3 H226 Flammable liquid and vapour.
Acute Tox. 4 H312 Harmful in contact with skin.
Acute Tox. 4 H332 Harmful if inhaled.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H335 May cause respiratory irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

>= 0.5% - < 1% 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime

REACH No.: 01-2119539477-28-XXXX, Index number: 616-014-00-0, CAS: 96-29-7, EC: 202-496-6
Carc. 2 H351 Suspected of causing cancer.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1,1A,1B H317 May cause an allergic skin reaction.
Acute Tox. 4 H312 Harmful in contact with skin.

>= 0.5% - < 1% Hydroxyphenyl-benzotriazole derivatives - EC number 400-830-7

REACH No.: 01-0000015075-76-xxxx, Index number: 607-176-00-3, CAS: 104810-48-2, EC: 400-830-7
Skin Sens. 1,1A,1B H317 May cause an allergic skin reaction.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

>= 0.1% - < 0.25% Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

REACH No.: 01-2119491304-40-XXXX, CAS: 111-20-6, EC: 915-687-0
Skin Sens. 1,1A,1B H317 May cause an allergic skin reaction.
Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

>= 0.01% - < 0.05% dipropyleneglycol methylether

CAS: 34590-94-8, EC: 252-104-2
Substance with a Union workplace exposure limit.

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Safety Data Sheet

ALTURA UV MAT

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

Give nothing to eat or drink.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire use CO₂ or chemical powder. Never use water.

Extinguishing media which must not be used for safety reasons:

Do not use water jets

None in particular.

5.2. Special hazards arising from the substance or mixture

Avoid inhaling the fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

Safety Data Sheet

ALTURA UV MAT

- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Adequately ventilated premises.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Always keep the containers tightly closed.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Adequately ventilated premises.
- 7.3. Specific end use(s)
See section 1.2

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
ACGIH - TWA: 1200 mg/m³, 197 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin
ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr
xylene [4] - CAS: 1330-20-7
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
AGS - TWA(8h): 221 mg/m³ - STEL((15 min)): 442 mg/m³ - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
AGS - TWA(8h): 221 mg/m³ - STEL((15 min)): 442 mg/m³ - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)
VLE1 - TWA(8h): 211 mg/m³, 50 ppm
VLE - STEL: 442 mg/m³, 100 ppm - Notes: Skin
dipropylenglycol methylether - CAS: 34590-94-8
EU - TWA(8h): 308 mg/m³, 50 ppm - Notes: Skin
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: Skin - Eye and URT irr, CNS impair
DNEL Exposure Limit Values
1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
Consumer: 3.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Professional: 369 ppm - Consumer: 43.9 ppm - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Professional: 50.6 mg/kg - Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

648.000/5

Page n. 5 of 13

Safety Data Sheet

ALTURA UV MAT

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/L

Target: Freshwater sediments - Value: 41.6 mg/kg

Target: Marine water sediments - Value: 4.17 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/L

Target: Soil (agricultural) - Value: 2.47 mg/kg

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/L

Target: Marine water - Value: 0.327 mg/L

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/L

Biological Exposure Index

xylene [4] - CAS: 1330-20-7

Value: 1.50 mg/L - medium: Blood - Sampling Period: End of turn

Value: 1.50 gg creatinina - medium: Blood - Sampling Period: End of turn

8.2. Exposure controls

Eye protection:

Use goggles/ facemask certified UNI EN 166.

Protection for skin:

Suitable protective clothing is required for complete skin protection: for example coveralls with long sleeves and trousers, rubber boots and apron, etc., according to UNI EN 14325.

Protection for hands:

Use protective gloves: waterproof rubber gloves certified UNI EN 374. Nitrile gloves provide good protection. Use care in selecting a penetration time of the gloves longer than the foreseen usage time.

Respiratory protection:

Use adequate protective respiratory equipment: a carbon filter mask with filters certified UNI EN 149 or dust masks certified UNI EN 140. Filters of types A and P types may be considered.

Thermal Hazards:

None

Environmental exposure controls:

See sections 6 and 13

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance : liquid

648.000/5

Page n. 6 of 13

Safety Data Sheet ALTURA UV MAT

Odour: N.A.
Colour: yellowish
pH: N.A.
Melting point / freezing point: N.A.
Boiling point (°C): bp>35 °C
Initial boiling point and boiling range: N.A.
Solid/gas flammability: N.A.
Upper/lower flammability or explosive limits: N.A.
Vapour density: N.A.
Flash point: 32 °C
Evaporation rate: N.A.
Vapour pressure: N.A.
Specific gravity (Kg/L) 20°C : 0.9386
Methodology: SPECIFIC WEIGHT BY MEANS OF PICNOMETER (gr / cm3).
Solubility in water: N.A.
Lipid solubility: N.A.
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Kinematic viscosity at 40°C (mm²/s): kv > 20,5
Viscosity (23°C±0.5°C): min 120 - max 160
Methodology: UNI EN ISO 2431 (ex DIN 53211 s)
Flow cup: DIN 4
Spindle: 0
Speed (rpm): 0

9.2. Other information

No further information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

ALTURA UV MAT

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

648.000/5

Page n. 7 of 13

Safety Data Sheet ALTURA UV MAT

- b) skin corrosion/irritation
Not classified
Based on available data, the classification criteria are not met
- c) serious eye damage/irritation
Not classified
Based on available data, the classification criteria are not met
- d) respiratory or skin sensitisation
Not classified
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met
- j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) acute toxicity:

Test: LC50 - Route: inhalation - Species: rat > 5000 mg/m³ - Duration: 4h - Source: OCSE 403

Test: LD50 - Route: oral - Species: rat > 5000 mg/kg - Source: OCSE 401

Test: LD50 - Route: oral - Species: rat > 5000 mg/kg - Source: OCSE 402

hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) acute toxicity:

Test: LC50 - Route: inhalation - Species: rat > 5000 mg/m³

Test: LD50 - Route: dermal - Species: rabbit > 3160 mg/kg

Test: LD50 - Route: oral - Species: rat > 5000 mg/kg

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat = 4.016 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 2000 mg/kg

Test: LC50 - Route: inhalation of vapours - Species: rat > 25.8 mg/l - Duration: 18207.6h

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 3523 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 2000 mg/kg

Test: LC50 - Route: inhalation - Species: rat > 27.571 mg/l - Duration: 4h

b) skin corrosion/irritation:

Test: Skin Irritant Positive

Safety Data Sheet

ALTURA UV MAT

c) serious eye damage/irritation:

Test: Eye Irritant Positive

dipropylenglycol methylether - CAS: 34590-94-8

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat = 8740.0 mg/kg

Test: LD50 - Route: dermal - Species: rabbit = 9510.0 mg/kg

Test: LC50 - Route: inhalation of vapours - Species: rat = 3404.47 mg/l

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ALTURA UV MAT

Not classified for environmental hazards

Based on available data, the classification criteria are not met

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) Aquatic acute toxicity:

Endpoint: NOEC - Species: Fish = 100 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 48

hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1028 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 3193 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 3198 mg/l - Duration h: 72

Endpoint: NOEC - Species: Algae > 3198 mg/l - Duration h: 72

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 ml/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56 d

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7 d

dipropylenglycol methylether - CAS: 34590-94-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 1919 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 969 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.5 mg/l - Duration h: 504

12.2. Persistence and degradability

There is no data available on the preparation itself.

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradability: Readily biodegradable - %: 80 - Notes: 28 d

648.000/5

Page n. 9 of 13

Safety Data Sheet

ALTURA UV MAT

hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradability: Readily biodegradable - %: 74 - Notes: 28 d

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable - Test: Dissolved organic carbon - %: 96 - Notes: 28 d

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable - Notes: solubilità in acqua=146 mg/l

dipropylenglycol methylether - CAS: 34590-94-8

Biodegradability: Readily biodegradable - Test: Oxygen consumption - %: 96 - Notes: 28 d

12.3. Bioaccumulative potential

There is no data available on the preparation itself.

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Bioaccumulation: Not bioaccumulative - Test: BCF - Bioconcentration factor - Notes: <2

xylene [4] - CAS: 1330-20-7

Test: Kow - Partition coefficient 3.2 - Notes: mg/l

Test: BCF - Bioconcentration factor 25.9 - Notes: mg/l

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime - CAS: 96-29-7

Test: Kow - Partition coefficient 0.59

Test: BCF - Bioconcentration factor 5

dipropylenglycol methylether - CAS: 34590-94-8

Bioaccumulation: Not bioaccumulative

12.4. Mobility in soil

There is no data available on the preparation itself.

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Mobility in soil: Mobile - Test: Koc 0.2-1.0

xylene [4] - CAS: 1330-20-7

Test: Koc 2.73 - Notes: mg/l

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Directives 91/156/CEE, 91/689/CEE, 94/62/CE.

EWC CODE 080111

Do not empty into drains, ground or waterways. Dispose of product residues and related containers at a collection point for hazardous or special waste or, where appropriate, through an authorized waste disposal company.

SECTION 14: Transport information

14.1. UN number

UN 1263

14.2 Proper shipping name: Paint

14.3 Transport hazard class(es) and Packing Group:

3 PG III

14.4. Environmental hazards

Marine Pollutant: -

14.5. Special precautions for user

648.000/5

Page n. 10 of 13

Safety Data Sheet

ALTURA UV MAT

None

Other informations

Land transport ADR/RID

Exemptions: ADR:2.2.3.1.5 - IMDG:2.3.2.5

ADR Classification code: F1

Maximum quantity for Limited Quantities: 5L/Kg

Tunnel code :D/E

Transport category: 3

Maritime transport (IMDG)

Exemptions: ADR:2.2.3.1.5 - IMDG:2.3.2.5

Maximum quantity for Limited Quantities: 5L/Kg

EmS number: F-E/S-E

Stowage provisions: A

Air transport(IATA/ICAO)

Exemptions: ADR:2.2.3.1.5 - IMDG:2.3.2.5

Maximum quantity for Limited Quantities: 5L/Kg

Pkg. inst. passenger and cargo aircraft: 309

Pkg. inst. cargo aircraft only: 310

Erg-code: 3L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 89/391/CEE and subsequent amendments (Risks related to chemical agents at work and Occupational exposure limit values). Directive 1999/13/EC and subsequent amendments (limitation of emissions of volatile organic compounds due to the use of organic solvents in certain activities and installations). Regulation (CE) n. 1907/2006 , Regulation (CE) 830/2015 and subsequent amendments (concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals - REACH). Regulation (CE) n.1272/2008 and subsequent amendments (on classification, labeling and packaging of substances and mixtures - CLP).
International Maritime Dangerous Goods Code, IATA Dangerous Goods Regulation, International Carriage of Dangerous Goods by Road (ADR).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restriction 3 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Restriction 40 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Where applicable, refer to the following regulatory provisions :

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation UE No 649/2012 concerning the export and import of dangerous chemicals.

Regulation UE n. 528/2012 concerning the making available on the market and use of biocidal products.

Directive 2012/18/EU (Seveso III)

Regulation (EC) No. 648/2004 (detergents).

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation (EC) No 689/2006 concerning the export and import of dangerous chemicals.

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

648.000/5

Page n. 11 of 13

Safety Data Sheet

ALTURA UV MAT

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

| Hazard class and hazard category | Code | Description |
|----------------------------------|---------------|--|
| Flam. Liq. 3 | 2.6/3 | Flammable liquid, Category 3 |
| Acute Tox. 4 | 3.1/4/Dermal | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 | 3.1/4/Inhal | Acute toxicity (inhalation), Category 4 |
| Asp. Tox. 1 | 3.10/1 | Aspiration hazard, Category 1 |
| Skin Irrit. 2 | 3.2/2 | Skin irritation, Category 2 |
| Eye Dam. 1 | 3.3/1 | Serious eye damage, Category 1 |
| Eye Irrit. 2 | 3.3/2 | Eye irritation, Category 2 |
| Skin Sens. 1,1A,1B | 3.4.2/1-1A-1B | Skin Sensitisation, Category 1,1A,1B |
| Carc. 2 | 3.6/2 | Carcinogenicity, Category 2 |
| STOT SE 3 | 3.8/3 | Specific target organ toxicity - single exposure, Category 3 |
| STOT RE 2 | 3.9/2 | Specific target organ toxicity - repeated exposure, Category 2 |
| Aquatic Acute 1 | 4.1/A1 | Acute aquatic hazard, category 1 |
| Aquatic Chronic 1 | 4.1/C1 | Chronic (long term) aquatic hazard, category 1 |
| Aquatic Chronic 2 | 4.1/C2 | Chronic (long term) aquatic hazard, category 2 |
| Aquatic Chronic 3 | 4.1/C3 | Chronic (long term) aquatic hazard, category 3 |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| Classification according to Regulation (EC) Nr. 1272/2008 | Classification procedure |
|---|--------------------------|
| Flam. Liq. 3, H226 | On basis of test data |
| STOT SE 3, H336 | Calculation method |

648.000/5

Page n. 12 of 13

Safety Data Sheet

ALTURA UV MAT

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

| | |
|-------------|--|
| ADR: | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| ATE: | Acute Toxicity Estimate |
| ATEmix: | Acute toxicity Estimate (Mixtures) |
| CAS: | Chemical Abstracts Service (division of the American Chemical Society). |
| CLP: | Classification, Labeling, Packaging. |
| DNEL: | Derived No Effect Level. |
| EINECS: | European Inventory of Existing Commercial Chemical Substances. |
| GefStoffVO: | Ordinance on Hazardous Substances, Germany. |
| GHS: | Globally Harmonized System of Classification and Labeling of Chemicals. |
| IATA: | International Air Transport Association. |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO: | International Civil Aviation Organization. |
| ICAO-TI: | Technical Instructions by the "International Civil Aviation Organization" (ICAO). |
| IMDG: | International Maritime Code for Dangerous Goods. |
| INCI: | International Nomenclature of Cosmetic Ingredients. |
| KSt: | Explosion coefficient. |
| LC50: | Lethal concentration, for 50 percent of test population. |
| LD50: | Lethal dose, for 50 percent of test population. |
| PNEC: | Predicted No Effect Concentration. |
| RID: | Regulation Concerning the International Transport of Dangerous Goods by Rail. |
| STEL: | Short Term Exposure limit. |
| STOT: | Specific Target Organ Toxicity. |
| TLV: | Threshold Limiting Value. |
| TWA: | Time-weighted average |
| WGK: | German Water Hazard Class. |