LOPOLIGHT



1nm tri-color, silver anodized

101-005

1nm tri-color, silver anodized Horizontally mounted with 0,75m cable

Specifications	
Number	101-005
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <u>www.lopolight.com under Service</u> <u>& Support</u>
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010307
IP rating	IP68
UPC Code	879343010300
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150
Current consumption (mA @ 24VDC)	81
Vessel size	Under 12M

LOPOLIGHT

Specifications	
Weight (Kg)	0.53 Kg
Weight (Oz)	18.69 Oz