



8 Litre Accumulator Tank

23240-2000

Features:

- Improves all multiple outlet pressure controlled water systems.
- Store of pressurised water maintains full flow when system demand temporarily exceeds pump capacity.
- Smoother flow, quieter water systems.
- Better control of hot water temperature.
- Longer pump life, lower battery drain.
- Integral rubber membrane eliminates maintenance and allows universal mounting.
- Fixed mounting bracket for robust installation.



Specifications

- Connections:** 3/4" BSP female thread.
Volume: 8 Litre (1 3/4 gallons).
Working pressure: 10 bar (140 psi) maximum.
Dimensions: 33cm high x 20cm wide x 22cm deep (13" x 8" x 8 1/2").
Net weight: 3.75 kg (8 1/4 lb).

Ordinary air may be used if it is necessary to increase the pressure. Replace the valve cap securely.

Installation Instructions

1. SETTING THE PRESSURE

The pressure must be adjusted before mounting the tank, which is delivered already pressurised with NITROGEN.



CAUTION - Nitrogen can cause oxygen starvation, ensure adequate ventilation Do not adjust the pressure in a confined space

Unscrew the valve cap to expose the valve. Using a pressure gauge, reduce the pressure to 0.2 bar (3 psi) below the pump cut-in pressure.

2. MOUNTING

The tank may be mounted at any angle without affecting its performance.

3. LOCATION

The tank should be connected to the outlet line from the water pump, using a "tee" piece in the line. The "tee" piece should be located before the outlet line divides to serve the hot water heater or other outlets. A short run of pipe may be used to connect the "tee" piece to the tank to allow it to be located in a convenient position but the total pipe run from the pump to the tank should be as short as possible.

4. SEALING

A good grade sealant or PTFE tape must be used on the 3/4" threaded male outlet to ensure a water and pressure tight connection.

Jabsco



ITT Industries

Jabsco, 1485 Dale Way, Costa Mesa, CA 92628-2158
 Tel : +1 714 545 8251 Fax : +1 714 957 0609

USA

Jabsco, Bingley Road, Hoddesdon, Hertfordshire, EN11 0BU
 Tel : +44 (0) 1992 450 145 Fax : +44 (0) 1992 467 132

UK

Fluid Products Canada, 55 Royal Road, Guelph, Ontario N1H 1T1
 Tel : +1 519 821 1900 Fax : +1 519 821 5316

CANADA

NHK Jabsco Co Ltd, 3-21-10, Shin - Yokohama, Kohoku-ku, Yokohama 222
 Tel : +81 (0) 45 475 8906 Fax : +81 (0) 45 475 8908

JAPAN

Jabsco GmbH, Oststraße 28, 22844 Norderstedt
 Tel : +49 (0) 40 53 53 73 0 Fax : +49 (0) 40 53 53 73 11

GERMANY

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.
 ©Copyright 2000 ITT Industries